Energy Efficiency Information			
Attribute	Symbol	Value	Units
Model Identification		EVC4	
Annual Energy Consumption	$AEC_{Hood}$	100	kWh
Time increase factor	f	1.5	
Fluid Dynamic Efficiency	FDE <sub>Hood</sub>	14.7 (D)	
Energy Efficiency Index	EEI <sub>Hood</sub>	91.0 (D)	
Measured airflow at Best Efficiency Point	Q <sub>BEP</sub>	281.4	m <sup>3</sup> /h
Measured Pressure at Best Efficiency Point	P <sub>BEP</sub>	248	Pa
Maximum airflow	Q <sub>MAX</sub>	503	m <sup>3</sup> /h
Measured electric power at Best Efficiency Point	W <sub>BEP</sub>	132	W
Nominal lighting power	WL	40	W
Average illumination of the lighting system on the cooking surface	E <sub>Middle</sub>	414	Lux
Measured power consumption in standby	P <sub>S</sub>	0.99	W
Measured power consumption off	Po	NA	W
mode Cound nouver lovel			
Sound power level	L <sub>WA</sub>	62	dBA
Grease Filter Efficiency	GFE <sub>Hood</sub>	45 (G)	%
Lamp efficiency	LE <sub>Hood</sub>	10.4 (E)	%