CDA
17:34
17:34
NIGELLA LAWSON
Nigel Slater
GOOD SHOPPING GUIDE
ETHICAL BUSINESS
LIFETIME
PARTS
WARRANTY
+2 YEARS LABOUR

ECP92BL Curved glass extractor

Colour:
Black



Features

- 3 speeds
- Ducted/re-circulating installation

Available in

- Stainless steel
- Black

Filters

- Aluminium grease filters
- Number of layers: 4
- Number of grease filters: 1
- Number of charcoal filters (optional): 1

Extraction rates and noise

- Extraction rate: 377m^3/hr
- Noise level: 61dBA
- Extraction rate at first speed: 224
- Extraction rate at second speed: 315
- Extraction rate at third speed: 377
- Noise level at first speed: 51
- Noise level at second speed: 58
- Noise level at third speed: 61

Technical specification

- Outlet diameter: 120mm/150mm
- Outlet diameter: It is best to use the AED6 (150mm) ducting kit rather than the AED5 (120mm) with the adaptor. This keeps noise levels to a minimum.
- Required height over electric hobs: 600mm (min)
- Required height over gas hobs: 700mm (min)
- Class I
- Fuse: 3A
- Mains Lead Length: 1m
- Mains lead rating: H05VV-F

Fitting notes

- Please ensure that you